



J SECTION



Part Number: 180J6
180 18.0" Nominal Outside Length
J J Belt Section
6 6 Ribs

The Poly-V® belt is a single, endless belt with longitudinal V-shaped ribs that mate consistently with the V-grooves in the sheaves. It combines the convenience of a thin, one-piece flat belt with the strong gripping traction of multiple V-belts to make the Poly-V® belt far better than either for many applications.


L SECTION



Part Number: 540L8
540 54.0" Nominal Outside Length
L L Belt Section
8 8 Ribs

More power in less space: Continuous engagement with the sheave driving surface gives you greater power capacity per inch of width. In addition, wasted space between separate V-belts is eliminated and converted into narrower, shallower grooves. These provide substantially greater contact area for stronger and more uniform traction.

M SECTION



Part Number: 990M10
990 99.0" Nominal Outside Length
M M Belt Section
10 10 Ribs

Longer belt and sheave life: Complete support of the tension member, combined with full and uniform engagement with the sheave grooves, eliminates differential driving and equalizes belt stresses. That, in turn, minimizes belt elongation and leads to significantly longer flex life.

POLY - V®

"J" SECTION POLY-V®

SIZE	WEIGHT BY COMMON RIB AMOUNTS IN POUNDS						LB PER RIB	MAX RIB
	4 RIB	6 RIB	8 RIB	10 RIB	16 RIB	20 RIB		
180J	0.04	0.06	0.08	0.10	0.16	0.20	0.01	68
190J	0.04	0.06	0.08	0.10	0.16	0.20	0.01	68
200J	0.04	0.06	0.08	0.10	0.16	0.20	0.01	68
220J	0.04	0.06	0.08	0.10	0.16	0.20	0.01	68
240J	0.04	0.06	0.08	0.10	0.16	0.20	0.01	68
260J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
280J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
300J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
320J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
340J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
360J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
380J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
400J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
410J	0.08	0.12	0.16	0.20	0.32	0.40	0.02	68
430J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
460J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
490J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
520J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
550J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
580J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
610J	0.12	0.18	0.24	0.30	0.48	0.60	0.03	68
650J	0.16	0.24	0.32	0.40	0.64	0.80	0.04	68
730J	0.16	0.24	0.32	0.40	0.64	0.80	0.04	68
870J	0.20	0.30	0.40	0.50	0.80	1.00	0.05	68
920J	0.20	0.30	0.40	0.50	0.80	1.00	0.05	68
980J	0.20	0.30	0.40	0.50	0.80	1.00	0.05	68

"L" SECTION POLY-V®

SIZE	WEIGHT BY COMMON RIB AMOUNTS IN POUNDS						LB PER RIB	MAX RIB
	6 RIB	8 RIB	10 RIB	12 RIB	14 RIB	16 RIB		
500L	0.66	0.88	1.10	1.32	1.54	1.76	0.11	96
540L	0.72	0.96	1.20	1.44	1.68	1.92	0.12	96
560L	0.72	0.96	1.20	1.44	1.68	1.92	0.12	96
615L	0.78	1.04	1.30	1.56	1.82	2.08	0.13	96
635L	0.84	1.12	1.40	1.68	1.96	2.24	0.14	96
655L	0.84	1.12	1.40	1.68	1.96	2.24	0.14	96
675L	0.90	1.20	1.50	1.80	2.10	2.40	0.15	96
695L	0.90	1.20	1.50	1.80	2.10	2.40	0.15	96
725L	0.96	1.28	1.60	1.92	2.24	2.56	0.16	96
765L	0.96	1.28	1.60	1.92	2.24	2.56	0.16	96
780L	1.02	1.36	1.70	2.04	2.38	2.72	0.17	96
795L	1.02	1.36	1.70	2.04	2.38	2.72	0.17	96
815L	1.02	1.36	1.70	2.04	2.38	2.72	0.17	96
840L	1.08	1.44	1.80	2.16	2.52	2.88	0.18	96
865L	1.08	1.44	1.80	2.16	2.52	2.88	0.18	96
915L	1.14	1.52	1.90	2.28	2.66	3.04	0.19	96
975L	1.26	1.68	2.10	2.52	2.94	3.36	0.21	96
990L	1.26	1.68	2.10	2.52	2.94	3.36	0.21	96
1065L	1.38	1.84	2.30	2.76	3.22	3.68	0.23	96
1120L	1.44	1.92	2.40	2.88	3.36	3.84	0.24	96
1150L	1.44	1.92	2.40	2.88	3.36	3.84	0.24	96
1215L	1.80	2.40	3.00	3.60	4.20	4.80	0.30	72
1230L	1.80	2.40	3.00	3.60	4.20	4.80	0.30	72
1295L	1.86	2.48	3.10	3.72	4.34	4.96	0.31	72
1310L	1.92	2.56	3.20	3.84	4.48	5.12	0.32	72
1455L	2.10	2.80	3.50	4.20	4.90	5.60	0.35	72

"M" SECTION POLY-V®

SIZE	WEIGHT BY COMMON RIB AMOUNTS IN POUNDS						LB PER RIB	MAX RIB
	6 RIB	8 RIB	10 RIB	12 RIB	14 RIB	16 RIB		
900M	4.20	5.60	7.00	8.40	9.80	11.20	0.70	36
940M	4.38	5.84	7.30	8.76	10.22	11.68	0.73	36
990M	4.62	6.16	7.70	9.24	10.78	12.32	0.77	36
1060M	4.92	6.56	8.20	9.84	11.48	13.12	0.82	36
1115M	6.18	8.24	10.30	12.36	14.42	16.48	1.03	36
1150M	6.36	8.48	10.60	12.72	14.84	16.96	1.06	36
1185M	6.54	8.72	10.90	13.08	15.26	17.44	1.09	36
1230M	6.78	9.04	11.30	13.56	15.82	18.08	1.13	36
1310M	6.92	9.16	11.40	13.68	15.96	18.24	1.14	74
1390M	6.48	8.64	10.80	12.96	15.12	17.28	1.08	74
1470M	6.84	9.12	11.40	13.68	15.96	18.24	1.14	74
1610M	7.44	9.92	12.40	14.88	17.36	19.84	1.24	74
1650M	7.62	10.16	12.70	15.24	17.78	20.32	1.27	74
1760M	8.16	10.88	13.60	16.32	19.04	21.76	1.36	74
1830M	8.46	11.28	14.10	16.92	19.74	22.56	1.41	74
1980M	9.12	12.16	15.20	18.24	21.28	24.32	1.52	74
2130M	9.78	13.04	16.30	19.56	22.82	26.08	1.63	74
2410M	11.04	14.72	18.40	22.08	25.76	29.44	1.84	74
2560M	11.70	15.60	19.50	23.40	27.30	31.20	1.95	74
2710M	12.36	16.48	20.60	24.72	28.84	32.96	2.06	74
3010M	13.74	18.32	22.90	27.48	32.06	36.64	2.29	74
3310M	15.06	20.08	25.10	30.12	35.14	40.16	2.51	74
3610M	16.38	21.84	27.30	32.76	38.22	43.68	2.73	74