



2L SECTION FHP BELTS: Top Width = 0.25" Thickness = 0.16"											
BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB
2L120	11.0	12.0	.02	2L190	18.0	19.0	.03	2L260	25.0	26.0	.04
2L140	13.0	14.0	.02	2L200	19.0	20.0	.03	2L300	29.0	30.0	.05
2L150	14.0	15.0	.02	2L220	21.0	22.0	.03	2L310	30.0	31.0	.05
2L160	15.0	16.0	.03	2L240	23.0	24.0	.04	2L320	31.0	32.0	.05
2L180	17.0	18.0	.03								




3L SECTION FHP BELTS: Top Width = 0.38" Thickness = 0.22"											
BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB
3L120	10.7	12.0	.04	3L320	30.7	32.0	.11	3L520	50.7	52.0	.17
3L130	11.7	13.0	.05	3L330	31.7	33.0	.11	3L530	51.7	53.0	.18
3L140	12.7	14.0	.05	3L340	32.7	34.0	.12	3L540	52.7	54.0	.18
3L150	13.7	15.0	.05	3L350	33.7	35.0	.12	3L550	53.7	55.0	.18
3L160	14.7	16.0	.06	3L360	34.7	36.0	.12	3L560	54.7	56.0	.19
3L170	15.7	17.0	.06	3L370	35.7	37.0	.12	3L570	55.7	57.0	.19
3L180	16.7	18.0	.06	3L380	36.7	38.0	.13	3L580	56.7	58.0	.19
3L190	17.7	19.0	.07	3L390	37.7	39.0	.13	3L590	57.7	59.0	.20
3L200	18.7	20.0	.07	3L400	38.7	40.0	.13	3L600	58.7	60.0	.20
3L210	19.7	21.0	.07	3L410	39.7	41.0	.14	3L610	59.7	61.0	.20
3L220	20.7	22.0	.08	3L420	40.7	42.0	.14	3L620	60.7	62.0	.21
3L230	21.7	23.0	.08	3L430	41.7	43.0	.14	3L630	61.7	63.0	.21
3L240	22.7	24.0	.08	3L440	42.7	44.0	.15	3L640	62.7	64.0	.21
3L250	23.7	25.0	.09	3L450	43.7	45.0	.15	3L650	63.7	65.0	.22
3L260	24.7	26.0	.09	3L460	44.7	46.0	.15	3L660	64.7	66.0	.22
3L270	25.7	27.0	.09	3L470	45.7	47.0	.16	3L670	65.7	67.0	.22
3L280	26.7	28.0	.10	3L480	46.7	48.0	.16	3L690	67.7	69.0	.23
3L290	27.7	29.0	.10	3L490	47.7	49.0	.16	3L730	71.7	73.0	.24
3L300	28.7	30.0	.10	3L500	48.7	50.0	.17	3L740	72.7	74.0	.25
3L310	29.7	31.0	.11	3L510	49.7	51.0	.17	3L760	74.7	76.0	.25



All "4L" Belts Feature ContiTech's Exclusive Molded Cog Design For Smoother, Cooler and Quieter Running Drives

4L SECTION FHP BELTS: Top Width = 0.50" Thickness = 0.31"											
BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB
4L150	13.0	15.0	.09	4L310	29.0	31.0	.16	4L470	45.0	47.0	.24
4L160	14.0	16.0	.08	4L320	30.0	32.0	.16	4L480	46.0	48.0	.24
4L170	15.0	17.0	.09	4L330	31.0	33.0	.17	4L490	47.0	49.0	.24
4L180	16.0	18.0	.09	4L340	32.0	34.0	.17	4L500	48.0	50.0	.25
4L190	17.0	19.0	.10	4L350	33.0	35.0	.18	4L510	49.0	51.0	.25
4L200	18.0	20.0	.10	4L360	34.0	36.0	.18	4L520	50.0	52.0	.26
4L210	19.0	21.0	.11	4L370	35.0	37.0	.19	4L530	51.0	53.0	.26
4L220	20.0	22.0	.11	4L380	36.0	38.0	.19	4L540	52.0	54.0	.27
4L230	21.0	23.0	.12	4L390	37.0	39.0	.20	4L550	53.0	55.0	.27
4L240	22.0	24.0	.12	4L400	38.0	40.0	.20	4L560	54.0	56.0	.28
4L250	23.0	25.0	.13	4L410	39.0	41.0	.21	4L570	55.0	57.0	.28
4L260	24.0	26.0	.13	4L420	40.0	42.0	.21	4L580	56.0	58.0	.29
4L270	25.0	27.0	.14	4L430	41.0	43.0	.22	4L590	57.0	59.0	.29
4L280	26.0	28.0	.14	4L440	42.0	44.0	.22	4L600	58.0	60.0	.30
4L290	27.0	29.0	.15	4L450	43.0	45.0	.23				
4L300	28.0	30.0	.15	4L460	44.0	46.0	.23				



All "5L" Belts Feature ContiTech's Exclusive Molded Cog Design For Smoother, Cooler and Quieter Running Drives

5L SECTION FHP BELTS: Top Width = 0.66" Thickness = 0.38"											
BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB	BELT NO.	INSIDE LGTH (IN.)	OUTS LGTH (IN)	FHP WT LB
5L230	20.0	23.0	.18	5L350	32.0	35.0	.27	5L470	44.0	47.0	.36
5L240	21.0	24.0	.19	5L360	33.0	36.0	.28	5L480	45.0	48.0	.37
5L250	22.0	25.0	.20	5L370	34.0	37.0	.29	5L490	46.0	49.0	.38
5L260	23.0	26.0	.20	5L380	35.0	38.0	.29	5L500	47.0	50.0	.38
5L270	24.0	27.0	.21	5L390	36.0	39.0	.30	5L510	48.0	51.0	.39
5L280	25.0	28.0	.22	5L400	37.0	40.0	.31	5L520	49.0	52.0	.40
5L290	26.0	29.0	.23	5L410	38.0	41.0	.32	5L530	50.0	53.0	.41
5L300	27.0	30.0	.23	5L420	39.0	42.0	.32	5L540	51.0	54.0	.41
5L310	28.0	31.0	.24	5L430	40.0	43.0	.33	5L550	52.0	55.0	.42
5L320	29.0	32.0	.25	5L440	41.0	44.0	.34	5L560	53.0	56.0	.43
5L330	30.0	33.0	.26	5L450	42.0	45.0	.35				
5L340	31.0	34.0	.26	5L460	43.0	46.0	.35				