




COGGED SIZES

3VX HY-T[®] WEDGE BELTS: Top Width = 0.38" Thickness = 0.31"

BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
3VX250	25.0	.11	3VX475	47.5	.20	3VX900	90.0	.37
3VX265	26.5	.11	3VX500	50.0	.21	3VX950	95.0	.39
3VX280	28.0	.12	3VX530	53.0	.22	3VX1000	100.0	.41
3VX300	30.0	.13	3VX560	56.0	.23	3VX1060	106.0	.44
3VX315	31.5	.13	3VX600	60.0	.25	3VX1120	112.0	.46
3VX335	33.5	.14	3VX630	63.0	.26	3VX1180	118.0	.49
3VX355	35.5	.15	3VX670	67.0	.28	3VX1250	125.0	.58
3VX375	37.5	.16	3VX710	71.0	.29	3VX1320	132.0	.61
3VX400	40.0	.17	3VX750	75.0	.31	3VX1400	140.0	.65
3VX425	42.5	.18	3VX800	80.0	.33	3VX1500	150.0	.62
3VX450	45.0	.19	3VX850	85.0	.35			

5VX HY-T[®] WEDGE BELTS: Top Width = 0.62" Thickness = 0.53"

BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
5VX450	45.0	.44	5VX680	68.0	.66	5VX1000	100.0	.97
5VX470	47.0	.46	5VX690	69.0	.67	5VX1030	103.0	1.00
5VX490	49.0	.48	5VX710	71.0	.69	5VX1060	106.0	1.03
5VX500	50.0	.49	5VX730	73.0	.71	5VX1080	108.0	1.04
5VX510	51.0	.50	5VX740	74.0	.72	5VX1120	112.0	1.08
5VX530	53.0	.52	5VX750	75.0	.73	5VX1150	115.0	1.11
5VX540	54.0	.53	5VX780	78.0	.76	5VX1180	118.0	1.14
5VX550	55.0	.54	5VX800	80.0	.78	5VX1230	123.0	1.46
5VX560	56.0	.55	5VX810	81.0	.79	5VX1250	125.0	1.49
5VX570	57.0	.56	5VX830	83.0	.81	5VX1320	132.0	1.58
5VX580	58.0	.57	5VX840	84.0	.82	5VX1400	140.0	1.67
5VX590	59.0	.58	5VX850	85.0	.83	5VX1500	150.0	1.79
5VX600	60.0	.59	5VX860	86.0	.84	5VX1600	160.0	1.91
5VX610	61.0	.60	5VX880	88.0	.85	5VX1700	170.0	2.02
5VX630	63.0	.62	5VX900	90.0	.87	5VX1800	180.0	2.14
5VX650	65.0	.64	5VX930	93.0	.90	5VX1900	190.0	2.26
5VX660	66.0	.64	5VX950	95.0	.92	5VX2000	200.0	2.38
5VX670	67.0	.65	5VX960	96.0	.93			



NONCOGGED SIZES

3V HY-T [®] WEDGE BELTS: Top Width = 0.38" Thickness = 0.31"								
BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
3V250 ENV	25.0	.12	3V475 ENV	47.5	.22	3V900 ENV	90.0	.42
3V265 ENV	26.5	.12	3V500 ENV	50.0	.23	3V950 ENV	95.0	.41
3V280 ENV	28.0	.13	3V530 ENV	53.0	.25	3V1000 ENV	100.0	.44
3V300 ENV	30.0	.14	3V560 ENV	56.0	.26	3V1060 ENV	106.0	.49
3V315 ENV	31.5	.15	3V600 ENV	60.0	.28	3V1120 ENV	112.0	.49
3V335 ENV	33.5	.16	3V630 ENV	63.0	.29	3V1180 ENV	118.0	.55
3V355 ENV	35.5	.17	3V670 ENV	67.0	.31	3V1250 ENV	125.0	.58
3V375 ENV	37.5	.18	3V710 ENV	71.0	.33	3V1320 ENV	132.0	.61
3V400 ENV	40.0	.19	3V750 ENV	75.0	.35	3V1400 ENV	140.0	.65
3V425 ENV	42.5	.20	3V800 ENV	80.0	.37			
3V450 ENV	45.0	.21	3V850 ENV	85.0	.37			

5V HY-T [®] WEDGE BELTS: Top Width = 0.62" Thickness = 0.53"								
BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
5V500 ENV	50.0	.59	5V1060 ENV	106.0	1.25	5V2000 ENV	200.0	2.38
5V560 ENV	56.0	.66	5V1120 ENV	112.0	1.32	5V2120	212.0	2.52
5V630 ENV	63.0	.74	5V1180 ENV	118.0	1.38	5V2240	224.0	2.66
5V670 ENV	67.0	.79	5V1250 ENV	125.0	1.49	5V2360	236.0	2.80
5V710 ENV	71.0	.84	5V1320 ENV	132.0	1.58	5V2500	250.0	2.97
5V750 ENV	75.0	.88	5V1400 ENV	140.0	1.67	5V2650	265.0	3.15
5V800 ENV	80.0	.94	5V1500 ENV	150.0	1.79	5V2800	280.0	3.32
5V850 ENV	85.0	1.00	5V1600 ENV	160.0	1.91	5V3000	300.0	3.56
5V900 ENV	90.0	1.06	5V1700 ENV	170.0	2.02	5V3150	315.0	3.75
5V950 ENV	95.0	1.12	5V1800 ENV	180.0	2.14	5V3350	335.0	3.98
5V1000 ENV	100.0	1.18	5V1900 ENV	190.0	2.26	5V3550	355.0	4.22

8V HY-T [®] WEDGE BELTS: Top Width = 1.00" Thickness = 0.91"								
BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB	BELT NO.	EFFECTIVE OUTSIDE LENGTH	WT LB
8V1000	100.0	3.06	8V1800	180.0	5.78	8V3150	315.0	9.64
8V1060	106.0	3.25	8V1900	190.0	6.10	8V3350	335.0	10.25
8V1120	112.0	3.43	8V2000	200.0	6.42	8V3550	355.0	10.86
8V1180	118.0	3.61	8V2120	212.0	6.80	8V3750	375.0	11.46
8V1250	125.0	3.82	8V2240	224.0	7.18	8V4000	400.0	12.23
8V1320	132.0	4.25	8V2360	236.0	7.57	8V4250	425.0	12.99
8V1400	140.0	4.51	8V2500	250.0	8.01	8V4500	450.0	13.75
8V1500	150.0	4.83	8V2650	265.0	8.49	8V4750	475.0	14.51
8V1600	160.0	5.15	8V2800	280.0	8.97	8V5000	500.0	15.27
8V1700	170.0	5.46	8V3000	300.0	9.60	8V5600	560.0	17.09